

1953 Triumph TR2	
Year	1953
Make	Triumph
Model	TR2
Engine Location	Front
Drive Type	Rear Wheel
Body Material	Steel body on steel frame
Production Years for Series	1953-1955
Price	\$2,448.00

Performance	
0-60 mph	11.9 seconds.
1/4 Mile	19.6 seconds
Top Speed	104 mph 167.3 km/h

Engine	
Engine Configuration	I
Cylinders	4
Aspiration/Induction	Normal
Displacement	1991.00 cc 121.5 cu in. 2 L.
Valvetrain	OHV
Horsepower	90.00 BHP (66.2 KW) @ 4800.00 RPM
Torque	117.00 Ft-Lbs (158.7 NM) @ 3000.00 RPM
HP / Liter	45.0 BHP / Liter
Bore	3.27 in 83.1 mm.
Stroke	3.62 in 91.9 mm.
Compression Ratio	8.5:1
Main Bearings	3
Fuel Feed	Carburetor
	2 SU Carburetor
Block	Cast-iron

Gear Ratios	
1st Gear	3.38:1
2nd Gear	2.00:1
3rd Gear	1.325:1
4th Gear	1.00:1

Standard Transmission	
Gears	4
Transmission	Manual
	Optional overdrive
Final Drive	3.7:1

Dimensions	
Seating Capacity	2

Doors	2
Exterior	
Length	151.001 in 3835.4 mm.
Width	55.501 in 1409.7 mm.
Height	50.001 in 1270 mm.
Wheelbase	88.001 in 2235.2 mm.
Front Track	45.001 in 1143 mm.
Rear Track	45.501 in 1155.7 mm.

Suspension	
Suspension	Front : Unequal-length A-arms with coil springs Rear : Rigid axle with semi-elliptic leaf springs

Steering	
	Cam and Lever

Tires / Wheels	
Tires	5.50x15
Wheels	Disc - wire were optional