

1960 Triumph TR3A	
Year	1960
Make	Triumph
Model	TR3A
Engine Location	Front
Drive Type	Rear Wheel
Production Years for Series	1957-1962
Weight	1990 lbs 902.7 kg

Performance	
0-60 mph	12 seconds.
Top Speed	109 mph 175.4 km/h

Engine	
Engine Configuration	S
Cylinders	4
Aspiration/Induction	Normal
Displacement	2138.00 cc 130.5 cu in. 2.1 L.
Valves	8 valves. 2 valves per cylinder.
Valvetrain	OHV
Horsepower	100.00 BHP (73.6 KW) @ 4600.00 RPM
Torque	130.00 Ft-Lbs (176.3 NM) @ 3350.00 RPM
HP to Weight Ratio	19.9 LB / HP
HP / Liter	47.6 BHP / Liter
Bore	3.39 in 86.1 mm.
Stroke	3.62 in 91.9 mm.
Compression Ratio	9.00:1

Transmission Information	
Gears	4
Transmission	Manual

Dimensions	
Seating Capacity	2
Doors	2
Exterior	
Length	151.001 in 3835.4 mm.
Width	55.501 in 1409.7 mm.
Height	50.001 in 1270 mm.
Wheelbase	88.101 in 2237.8 mm.
Front Track	49.001 in 1244.6 mm.
Rear Track	49.001 in 1244.6 mm.