

| 1961 Triumph TR3A | |
|-----------------------------|---------------------------|
| Year | 1961 |
| Make | Triumph |
| Model | TR3A |
| Engine Location | Front |
| Drive Type | Rear Wheel |
| Body Material | Steel body on steel frame |
| Production Years for Series | 1957-1962 |

| Performance | |
|-------------|----------------------|
| 0-60 mph | 12.5 seconds. |
| Top Speed | 102 mph 164.1 km/h |

| Engine | |
|----------------------|--|
| Engine Configuration | I |
| Cylinders | 4 |
| | Solid valve lifters |
| Aspiration/Induction | Normal |
| Displacement | 121.50 CU IN. 1991.4 cc. 2 L. |
| Valvetrain | OHV |
| Horsepower | 100.00 BHP (73.6 KW) @ 5000.00 RPM |
| Torque | 117.00 Ft-Lbs (158.7 NM) @ 3000.00 RPM |
| HP / Liter | 50.0 BHP / Liter |
| Bore | 3.27 in 83.1 mm. |
| Stroke | 3.62 in 91.9 mm. |
| Compression Ratio | 8.5:1 |
| Main Bearings | 3 |
| Fuel Type | Gasoline - Petrol |
| Fuel Feed | 2 SU Carburetor |
| Block | Cast-iron |

| Standard Transmission | |
|-----------------------|--------|
| Gears | 4 |
| Transmission | Manual |
| Final Drive | 3.7:1 |

| Dimensions | |
|------------------|---|
| Seating Capacity | 2 |

| Suspension | |
|------------|--|
| Suspension | Front : Unequal-length A-arms with coil springs Rear : Rigid axle with semi-elliptic leaf springs |

| Steering | |
|----------|---------------|
| | Cam and Lever |

Tires / Wheels

Tires

5.50x15